# Bartholomew Engineering, Inc.

Environmental Civil Water/Wastewater Subdivisions Surveying

4120 North 20th Street Suite F
Phoenix, Arizona 85016
(602) 957-0208
(602) 956-3690 FAX

Richard F. Bartholomew, P.E., R.L.S.
President



August 13, 1993

Mr. Craig Cooper
U.S. EPA Region IX
75 Hawthorne Street, H-7-2
San Francisco, CA 94105

RE: PGA OPERABLE UNIT 16; PHOENIX-GOODYEAR AIRPORT SUPERFUND SITE
SECOND QUARTER REPORT -- NO. 1993-2
APRIL, MAY, JUNE 1993
Job No. 731189

Dear Craig,

In accordance with the approved reporting schedule we are transmitting the referenced report items.

- PGA OPERABLE UNIT 16 OPERATIONS SECOND 1993 QUARTERLY REPORT
- MONITORING WELL WATER LEVEL AND CHEMICAL ANALYSIS REPORT, PRINTED DATA REPORT (EPA), COMPUTER DISK-FOXPRO-DATABASE (URS ONLY)
- TREATMENT PLANT AND INFLUENT AND EFFLUENT CHEMICAL ANALYSIS REPORT, PRINTED DATA REPORT (EPA), COMPUTER DISK-FOXPRO-DATABASE (URS ONLY)
- PRINTS AND ACETATE OVERLAYS MAPS FOR TCE CONCENTRATIONS (ISOPLETHS MAP) AND SUBUNIT A GROUNDWATER ELEVATIONS (CONTOUR) MAPS, JUNE 1993 DATABASE.

Please contact us if you have any questions or need further information.

Sincerely,

Richard F. Bartholomew

Richard F. Bartholomew, P.E.

cc: Edward P. Waltz, The Goodyear Tire & Rubber Co. (letter, report and prints)

Larry Smith, URS Consultants (letter, prints, and computer disk of FoxPro database)

Todd Struttman, Sharp & Associates (letter, report, disk, overlays, prints, and printed data)

Cynthia Parker, City of Phoenix (letter, report, and printed data)

Donn Stoltzfus, City of Phoenix (letter, report, overlays, prints, and printed data).

Enclosures

# PGA-OPERABLE UNIT 16 SECOND QUARTER REPORT NO. 1993-2
## REPORT PERIOD - APRIL, MAY, JUNE, 1993
(April 1, 1993 - June 31, 1993)

**SUMMARY**

- TOTAL WATER TREATED DURING QUARTER - 72,864,802 (gallons)
- TOTAL WATER TREATED TO DATE - 609,203,494 (gallons)
- TCE LEVELS - ug/l (ppb)

| | INFLUENT | EFFLUENT |
|---|---|---|
| April (4/14/93) | 150 | 2.8 |
| May (5/26-5/28) | 220 | 2.9 |
| June (6/7/93) | 230* | 3.55* |

*Average value (6/23/93)

- DAYS OF OPERATIONS -- 70 days out of 91 days in period.
- ZONE OF CAPTURE -- Approximately 2' depth around Extraction Wells NE-1 through NE-5
- ESTIMATED POUNDS OF TCE REMOVED THIS PERIOD - 119.54
- ESTIMATED POUNDS OF TCE REMOVED TO DATE - ESTIMATED 955.30
- ESTIMATED GALLONS OF TCE REMOVED TO DATE - 77.67

**DETAILED REPORT**

| MONTH | APRIL | MAY | JUNE |
|---|---|---|---|
| Total Water Extracted, gallons | 25,481,770 | 15,133,968 | 32,249,064 |
| Total Water Reinjected, gallons | 24,653,640 | 14,755,665 | 31,456,310 |
| average Flow, gpm | 632 | 751 | 803 |
| Days of Plant Operation | 28 | 14 | 28 |
| **Treated Plant TCE levels (ug/l)** | | | |
| A. Influent | 150 | 220 | 230 |
| B. Effluent | 2.8 | 2.9 | 3.55 |
| C. Percent Reduction | 98.13 | 98.68 | 98.46 |
| D. Estimated Total TCE Removed (pounds) | 31.23 | 27.40 | 60.91 |
| E. Estimated Average TCE Removed (pounds per day) | 1.12 | 1.96 | 2.18 |

## OPERATIONAL COMMENTS

### EXTRACTION WELLS

- Wells No. NE-1, 2, 3, 4, 5 and E-7, 8, 10, 11, and E-12 operated during the quarterly period as shown below.

- EXTRACTION WELL OPERATIONAL DATA THIS QUARTER:

| Well No. | Average GPM | Operational Days this Quarter |
|---|---|---|
| NE-1 | 122 | 70 |
| NE-2 | 70 | 70 |
| NE-3 | 104 | 70 |
| NE-4 | 90 | 70 |
| NE-5 | 104 | 70 |
| E-7 | 3 | 70 |
| E-8 | 28 | 70 |
| E-10 | 55 | 70 |
| E-11 | 95 | 70 |
| E-12 | 102 | 70 |
| TOTAL | 728 GPM | |

- AVERAGE GPM FOR QUARTERLY PERIOD = 728

- Motors on Wells NE-3 and NE-8 found to be defective and were replaced.

### PLANT OPERATIONS

- The carbon air treatment was in operation each operational day during the quarter.

- The plant acid piping system was completely replaced with teflon piping and valves to prevent future acid line leaks. The plant was out of service for 14 days to replace the acid piping system and clean out the acid containment vault.

- Tests have been completed to evaluate the air stripping tower efficiency. The air flow was measured throughout the treatment plant. Samples of the water influent and effluent were taken for TCE levels. Results of the samples are shown on the attached summary. During the Tower evaluation and modification period the tower was out of service 7 days. Two days for packing additional placement and five days spread over May and June for testing.

  Based upon the study, RE Wright and Environmental Restoration System recommended that an additional 18" of packing be added to the top of the

town and the inlet piping be modified to better distribute the influent (extraction) water across the top of the tower. The additional packing was added to the tower and the inlet piping will be added during July. Sample results show a slight improvement. However, the designers are continuing to evaluate the tower packing and water distribution to improve the treatment efficiency.

INJECTION WELLS

- Eight, Phase II injection Wells were in operation during this period. The injection system averaged 654 GPM. Approximately 74 GPM (10.2%) was lost through evaporation and meter losses.

- Eight injection wells are being held in reserve.

ZONE OF CAPTURE

- The water level map prepared for this quarter shows that the zone of capture has been re-established along the extraction wells NE-1 through NE-5. The zone of capture near well E-12 is limited to the immediate well area as indicated by the change in the water level contour lines near well E-12.

TCE LEVEL REDUCTION

- During this period 119.54 pounds of TCE was estimated to have been removed from the Sub Unit A groundwater.

- To date, it is estimated that 955.30 pounds of TCE have been removed from the Sub Unit A groundwater. This is approximately 77.67 gallons.

- The current average removal rate is 1.75 pounds per day.

DAYS IN OPERATION

- Days in operation during reporting period was 86.94 days out of 91 days during the quarterly period.

| Reason for Plant Out of Service | Days | Corrective Action Taken |
|---|---|---|
| Break in acid piping at storage tank | 14 | Replace entire acid piping system between tank and pumps with teflon tubing and teflon and viton lined valves. |
| Testing and evaluation air stripping tower to improve treatment efficiency and to add more packing material | 7 | Added additional packing material (Jaeger Packing) |

MONITORING WELLS

- Completed monthly, quarterly, and semi-annual water level and sampling of Sub-Unit A and B/C monitoring wells in accordance with the EPA approved monitoring plan.
- Completed monthly water level measurements of Sub-Unit A monitoring wells in 2 day period to determine zone of capture.
- Assisted attorney in preparation of access agreements for Monitoring wells EMW-25A and EMW-26A.

# TOWER REPORT

AIR STRIPPING TOWER DATA REVIEW 13-Aug-93 

| DATE | TCE INFL (ppb) | TCE EFFL (ppb) | WATER FLOW (gpm) | AIR FLOW (cfm) | AIR TO WATER RATIO | TOWER % EFFIC | COMMENTS |
|---|---|---|---|---|---|---|---|
| 02/07/90 | 230 | 1.9 | 354 | 2826 | 59.71 | 99.17 | |
| 02/15/90 | 340 | 1.0 | 452 | 3140 | 51.96 | 99.71 | |
| 02/20/90 | 300 | 1.0 | 318 | 2826 | 66.47 | 99.67 | |
| 05/25/90 | 245 | 3.1 | 471 | 3925 | 62.33 | 98.73 | |
| 06/20/90 | 380 | 2.5 | 290 | 4239 | 109.34 | 99.34 | |
| 07/18/90 | 340 | 2.6 | 398 | 4082 | 76.72 | 99.24 | |
| 08/17/90 | 340 | 2.8 | 480 | 3517 | 54.81 | 99.18 | |
| 09/23/90 | 370 | 0.8 | 371 | 3925 | 79.13 | 99.78 | |
| 10/18/90 | 220 | 1.0 | 404 | 3768 | 69.76 | 99.55 | |
| 11/25/90 | 490 | 1.8 | 400 | 3768 | 70.46 | 99.63 | |
| 12/18/90 | 300 | 1.5 | 485 | 3925 | 60.53 | 99.50 | |
| 01/23/91 | 191 | 1.8 | 450 | 4019 | 66.80 | 99.06 | |
| 02/17/91 | 150 | 1.7 | 490 | 3717 | 56.74 | 98.87 | |
| 03/17/91 | 210 | 1.2 | 349 | 4019 | 86.14 | 99.43 | |
| 04/22/91 | 210 | 1.1 | 393 | 4082 | 77.69 | 99.48 | |
| 05/22/91 | 210 | 1.8 | 428 | 3768 | 65.85 | 99.14 | |
| 06/20/91 | 240 | 1.7 | 262 | 4082 | 116.54 | 99.29 | |
| 07/12/91 | 240 | 1.7 | 406 | 3611 | 66.53 | 99.29 | |
| 07/21/91 | 250 | 1.2 | 411 | 3799 | 69.14 | 99.52 | |
| 08/19/91 | 227 | 1.9 | 427 | 3768 | 66.01 | 99.16 | |
| 09/22/91 | 170 | 1.0 | 409 | 3768 | 68.91 | 99.41 | |
| 01/19/92 | 200 | 0.9 | 320 | 3454 | 80.74 | 99.55 | |
| 03/19/92 | 180 | 2.5 | 361 | 3768 | 78.07 | 98.61 | |
| 05/15/92 | 160 | 4.6 | 567 | 4082 | 53.85 | 97.13 | (1) |
| 05/27/92 | 287 | 2.4 | 518 | 4082 | 58.94 | 99.16 | (2) |
| 06/19/92 | 160 | 2.4 | 376 | 3768 | 74.96 | 98.50 | (3) |
| 07/13/92 | 250 | 1.8 | 391 | 3611 | 69.08 | 99.28 | |
| 07/22/92 | 250 | 2.4 | 452 | 3768 | 62.36 | 99.04 | |
| 08/20/92 | 150 | 2.3 | 490 | 3768 | 57.52 | 98.47 | |
| 09/22/92 | 160 | 2.6 | 500 | 4082 | 61.07 | 98.38 | |
| 10/02/92 | 200 | 1.2 | 450 | 3768 | 62.63 | 99.40 | |
| 11/10/92 | 180 | 4.4 | 488 | 3454 | 52.94 | 97.56 | (4) |
| 11/17/92 | 160 | 3.9 | 568 | 3768 | 49.62 | 97.56 | |
| 11/24/92 | 260 | 4.6 | 578 | 3611 | 46.73 | 98.23 | (5) |
| 12/01/92 | 220 | 4.0 | 578 | 3768 | 48.76 | 98.18 | (6) |
| 12/09/92 | 200 | 3.1 | 591 | 5338 | 67.56 | 98.45 | |
| 01/30/93 | 220 | 3.6 | 564 | 5338 | 70.79 | 98.36 | |
| 02/22/93 | 210 | 2.6 | 561 | 5495 | 73.27 | 98.76 | |
| 03/15/93 | 220 | 4.0 | 679 | 5966 | 65.72 | 98.18 | |
| 03/25/93 | 180 | 8.2 | 557 | 5966 | 80.12 | 95.44 | (13) |
| 04/14/93 | 150 | 2.8 | 636 | 5024 | 59.09 | 98.13 | |
| 05/14/93 | 200 | 4.6 | 708 | 5809 | 61.37 | 97.70 | (7) |
| 05/14/93 | 210 | 13.0 | 740 | 5909 | 59.73 | 93.81 | (7)(8)(13) |
| 05/19/93 | NS | 5.8 | 800 | 6280 | 58.72 | 97.24 | (7)(13) |
| 05/19/93 | NS | 6.0 | 800 | 6280 | 58.72 | 97.14 | (7)(8)(13) |
| 05/19/93 | NS | 6.6 | 800 | 6280 | 58.72 | 96.86 | (7)(8)(13) |
| 05/20/93 | 190 | 4.9 | 820 | 6526 | 59.53 | 97.42 | (7)(13) |
| 05/21/93 | 140 | 2.1 | 586 | 6526 | 83.30 | 98.50 | (7)(9) |

| DATE | TCE INFL (ppb) | TCE EFFL (ppb) | WATER FLOW (gpm) | AIR FLOW (cfm) | AIR TO WATER RATIO | TOWER % EFFIC | COMMENTS |
|---|---|---|---|---|---|---|---|
| 05/21/93 | 220 | 7.2 | 820 | 4500 | 41.05 | 96.73 | (7)(13) |
| 05/22/93 | 220 | 6.0 | 820 | 4500 | 41.05 | 97.27 | (7)(13) |
| 05/24/93 | NS | 4.4 | 820 | 6280 | 57.29 | 98.00 | (7) |
| 05/24/93 | NS | 6.0 | 820 | 4500 | 41.05 | 97.27 | (7)(13) |
| 05/24/93 | NS | 4.3 | 820 | 6280 | 57.29 | 98.05 | (7) |
| 05/26/93 | 220 | 4.4 | 820 | 6280 | 57.29 | 98.00 | (7) |
| 05/28/93 | NS | 3.2 | 820 | 6280 | 57.29 | 98.55 | (7) |
| 05/28/93 | NS | 4.3 | 820 | 6908 | 63.01 | 98.05 | (7)(M) |
| 05/31/93 | NS | 2.5 | 820 | 6280 | 57.29 | 98.86 | (7) |
| 05/31/93 | NS | 3.8 | 820 | 6594 | 60.15 | 98.27 | (7)(M) |
| 06/01/93 | NS | 3.7 | 820 | 6437 | 58.72 | 98.32 | (7)(M) |
| 06/01/93 | NS | 3.9 | 820 | 6123 | 55.85 | 98.23 | (7)(M) |
| 06/01/93 | NS | 4.1 | 820 | 5589 | 50.98 | 98.14 | (7)(M) |
| 06/01/93 | NS | 5.1 | 820 | 5118 | 46.69 | 97.68 | (7)(M)(13) |
| 06/01/93 | NS | 10.0 | 820 | 4647 | 42.39 | 95.45 | (7)(M)(13) |
| 06/01/93 | NS | 14.0 | 820 | 4144 | 37.80 | 93.64 | (7)(M)(13) |
| 06/01/93 | NS | 4.5 | 820 | 6594 | 60.15 | 97.95 | (7)(M) |
| 06/01/93 | NS | 4.5 | 820 | 6280 | 57.29 | 97.95 | (7)(M) |
| 06/01/93 | NS | 4.9 | 820 | 5620 | 51.27 | 97.77 | (7)(M)(13) |
| 06/01/93 | NS | 5.2 | 820 | 5149 | 46.97 | 97.64 | (7)(M)(13) |
| 06/01/93 | NS | 6.9 | 820 | 4647 | 42.39 | 96.86 | (7)(M)(13) |
| 06/01/93 | NS | 7.8 | 820 | 4144 | 37.80 | 96.45 | (7)(M)(13) |
| 06/01/93 | NS | 2.5 | 820 | 6437 | 58.72 | 98.86 | (7) |
| 06/01/93 | NS | 3.8 | 820 | 6437 | 58.72 | 98.27 | (7) |
| 06/01/93 | NS | 4.3 | 820 | 6437 | 58.72 | 98.05 | (7) |
| 06/02/93 | 170 | 3.1 | 820 | 6437 | 58.72 | 98.18 | (7) |
| 06/04/93 | 180 | 3.4 | 800 | 3297 | 30.83 | 98.11 | |
| 06/07/93 | 210 | 3.0 | 800 | 6280 | 58.72 | 98.57 | |
| 06/09/93 | 200 | 3.3 | 800 | 6908 | 64.59 | 98.35 | (7) |
| 06/09/93 | 240 | 3.6 | 800 | 6908 | 64.59 | 98.50 | (7) |
| 06/09/93 | 210 | 3.8 | 800 | 6908 | 64.59 | 98.19 | (7) |
| 06/09/93 | 230 | 3.6 | 820 | 6908 | 63.01 | 98.43 | (7) |
| 06/10/93 | 250 | 8.6 | 840 | 6908 | 61.51 | 96.56 | (13) |
| 06/10/93 | 250 | 6.7 | 840 | 6908 | 61.51 | 97.32 | (7)(13) |
| 06/11/93 | 200 | 4.7 | 840 | 6908 | 61.51 | 97.65 | (7) |
| 06/11/93 | 140 | 4.8 | 840 | 6908 | 61.51 | 96.57 | (7) |
| 06/11/93 | 120 | 5.6 | 840 | 6908 | 61.51 | 95.33 | (7)(13) |
| 06/11/93 | 130 | 5.7 | 840 | 6908 | 61.51 | 95.62 | (7)(13) |
| 06/11/93 | 190 | 4.9 | 840 | 6908 | 61.51 | 97.42 | (7)(13) |
| 06/11/93 | 210 | 5.6 | 840 | 6908 | 61.51 | 97.33 | (7)(13) |
| 06/13/93 | 180 | 1.3 | 450 | 6280 | 104.39 | 99.28 | |
| 06/14/93 | 180 | 1.3 | 450 | 6280 | 104.39 | 99.28 | (10) |
| 06/15/93 | 200 | 0.7 | 480 | 6280 | 97.86 | 99.65 | (10) |
| 06/15/93 | NS | 0.8 | 480 | 6280 | 97.86 | 99.60 | |
| 06/16/93 | 210 | 0.9 | 490 | 6280 | 95.87 | 99.57 | (10) |
| 06/17/93 | 210 | 1.5 | 550 | 6280 | 85.41 | 99.29 | (11) |
| 06/18/93 | 210 | 2.0 | 590 | 6280 | 79.62 | 99.05 | (12) |
| 06/23/93 | 240 | 4.1 | 820 | 6280 | 57.29 | 98.29 | |

| DATE | TCE INFL (ppb) | TCE EFFL (ppb) | WATER FLOW (gpm) | AIR FLOW (cfm) | AIR TO WATER RATIO | TOWER % EFFIC | COMMENTS |
|---|---|---|---|---|---|---|---|
| 06/23/93 | 190 | 4.1 | 820 | 6280 | 57.29 | 97.84 | |
| 06/24/93 | 200 | 4.1 | 732 | 6280 | 64.17 | 97.95 | |
| 06/25/93 | 130 | 3.4 | 732 | 6908 | 70.59 | 97.38 | |
| 06/25/93 | 170 | 3.4 | 732 | 6908 | 70.59 | 98.00 | |
| 07/09/93 | NS | 2.0 | 820 | 6280 | 57.29 | 98.82 | |
| 07/09/93 | NS | 3.4 | 820 | 6280 | 57.29 | 98.00 | |
| 07/12/93 | 220 | 2.6 | 840 | 6280 | 55.92 | 98.47 | |
| 07/19/93 | 220 | 4.1 | 860 | 5000 | 43.49 | 98.14 | |

NOTES

1. Started E-12 trial run.
2. Treatment okay with higher TCE.
3. Installed new 15 HP blower on tower.
4. VIC unit and well E-12 on trial run.
5. Well E-12 on.
6. VIC unit & well E-12 on after air was increased.
7. Experimental samples to test tower efficiency. All wells on.
8. VIC unit off.
9. Wells NE-5 and E-12 off.
10. Wells NE-1, NE-2, NE-3, NE-4, and NE-5 on.
11. Wells NE-1, NE-2, NE-3, NE-4, NE-5, and E-10 on.
12. Wells NE-1, NE-2, NE-3, NE-4, NE-5, E-8, and E-10 on.
13. Sample was taken during tower tests under controlled conditions where the effluent water flow and air flow were being changed to evaluate the tower efficiency under varying conditions. Test runs were of short duration under 1-2 hours to allow for stabilization of flow conditions only. Tower operation was returned to normal flow rate once the tests and sample collection was completed.

VIC unit is on unless noted otherwise.
NS = No Sample; Used previous day influent level in calculations.
M = Mobile laboratory test.

# SUB UNIT A GROUNDWATER LEVEL CHANGES DURING SECOND QUARTERLY PERIOD

07/16/93

PHOENIX-GOODYEAR AIRPORT SITE
WATER LEVELS SUBUNIT A WELLS
COMPARISON OF MAY AND JUNE LEVELS

| WELL NAME | MEAS.PT ELEVATION | DEPTH TO WATER 05/18/93 | WATER TABLE ELEVATION 05/18/93 | DEPTH TO WATER 06/10/93 | WATER TABLE ELEVATION 06/10/93 | DELTA 6/10-5/18 |
|---|---|---|---|---|---|---|
| 15GMW-4 | 965.00 | 46.2 | 918.8 | 46.1 | 918.9 | 0.1 |
| 15GMW-5 | 959.45 | 40.6 | 918.9 | 40.4 | 919.1 | 0.2 |
| 16EMW-10 | 957.85 | 46.1 | 911.8 | 45.8 | 912.1 | 0.3 |
| 16EMW-11 | 958.49 | 47.8 | 910.7 | 47.3 | 911.2 | 0.5 |
| 16EMW-12 | 957.80 | 47.0 | 910.8 | 48.3 | 909.5 | -1.3 |
| 16EMW-14 | 956.61 | 48.4 | 908.2 | 48.4 | 908.2 | 0.0 |
| 16EMW-15 | 958.14 | 51.7 | 906.4 | 51.5 | 906.6 | 0.2 |
| 16EMW-16 | 962.40 | 54.4 | 908.0 | 53.8 | 908.6 | 0.6 |
| 16EMW-17 | 970.10 | 60.6 | 909.5 | 59.7 | 910.4 | 0.9 |
| 16EMW-3 | 962.97 | 50.0 | 913.0 | 49.9 | 913.1 | 0.1 |
| 16EMW-4 | 960.36 | 47.2 | 913.2 | 47.1 | 913.3 | 0.1 |
| 16EMW-5 | 966.39 | 54.6 | 911.8 | 54.6 | 911.8 | 0.0 |
| 16EMW-6 | 960.06 | 47.3 | 912.8 | 47.4 | 912.7 | -0.1 |
| 16EMW-7 | 960.04 | 49.1 | 910.9 | 49.2 | 910.8 | -0.1 |
| 16EMW-8 | 961.92 | 49.4 | 912.5 | 49.1 | 912.8 | 0.3 |
| 16EP-1 | 963.05 | 50.3 | 912.8 | 50.7 | 912.3 | -0.4 |
| 16EP-2 | 955.42 | 47.1 | 908.3 | 47.0 | 908.4 | 0.1 |
| 16EP-4 | 952.33 | 41.2 | 911.1 | 41.3 | 911.0 | -0.1 |
| 16GMW-3 | 962.20 | 46.7 | 915.5 | 46.4 | 915.8 | 0.3 |
| 16GMW-6 | 962.97 | 48.1 | 914.9 | 48.0 | 915.0 | 0.1 |
| 16GMW-7 | 962.84 | 45.9 | 916.9 | 45.6 | 917.2 | 0.3 |
| 16GMW-8 | 964.26 | 50.8 | 913.5 | 50.5 | 913.8 | 0.3 |
| 16GP-1 | 960.07 | 44.7 | 915.4 | 44.6 | 915.5 | 0.1 |
| 16GP-2 | 962.95 | 49.3 | 913.7 | 49.2 | 913.8 | 0.1 |
| 16GP-7 | 964.03 | 49.4 | 914.6 | 49.9 | 914.1 | -0.5 |
| 21EMW-13 | 950.71 | 44.2 | 906.5 | 44.7 | 906.0 | -0.5 |
| 21EP-3 | 940.75 | 38.1 | 902.7 | 38.6 | 902.2 | -0.5 |
| EMW-23A | 934.83 | 33.5 | 901.3 | 32.5 | 902.3 | 1.0 |
| EMW-24A | 942.82 | 40.4 | 902.4 | 40.2 | 902.6 | 0.2 |
| EMW-25A | 935.25 | 39.2 | 896.1 | 39.7 | 895.6 | -0.5 |
| EMW-26A | 950.88 | 46.0 | 904.9 | 46.7 | 904.2 | -0.7 |
| EMW-29A | 971.80 | 59.5 | 912.3 | 59.1 | 912.7 | 0.4 |
| EO-1 | 944.35 | 42.8 | 901.6 | 43.1 | 901.3 | -0.3 |
| EO-2 | 945.34 | 42.9 | 902.4 | 43.5 | 901.8 | -0.6 |
| EO-3 | 944.89 | 43.2 | 901.7 | 44.3 | 900.6 | -1.1 |
| EO-4 | 946.73 | 42.5 | 904.2 | 42.9 | 903.8 | -0.4 |
| EO-5 | 950.09 | 44.2 | 905.9 | 44.5 | 905.6 | -0.3 |
| EO-6 | no well | | 0.0 | | 0.0 | 0.0 |
| EO-7 | 957.87 | 47.8 | 910.1 | 47.7 | 910.2 | 0.1 |
| EO-8 | 959.12 | 46.8 | 912.3 | 46.7 | 912.4 | 0.1 |
| EO-9 | no well | | 0.0 | | 0.0 | 0.0 |
| EO-10 | 961.22 | 48.7 | 912.5 | 48.9 | 912.3 | -0.2 |
| EO-12 | 956.75 | 47.2 | 909.6 | 45.5 | 911.3 | 1.7 |
| E-3 | 941.54 | 38.1 | 903.4 | 39.0 | 902.5 | -0.9 |
| E-4 | 940.07 | 33.0 | 907.1 | 36.5 | 903.6 | -3.5 |
| E-10 | 957.56 | 46.0 | 911.6 | 45.2 | 912.4 | 0.8 |
| IO-1 | 934.35 | 32.2 | 902.2 | 31.5 | 902.9 | 0.7 |
| IO-2 | 930.51 | 27.7 | 902.8 | 26.4 | 904.1 | 1.3 |

07/16/93

PHOENIX-GOODYEAR AIRPORT SITE
WATER LEVELS SUBUNIT A WELLS
COMPARISON OF MAY AND JUNE LEVELS

| WELL NAME | MEAS.PT ELEVATION | DEPTH TO WATER 05/18/93 | WATER TABLE ELEVATION 05/18/93 | DEPTH TO WATER 06/10/93 | WATER TABLE ELEVATION 06/10/93 | DELTA 6/10-5/18 |
|---|---|---|---|---|---|---|
| IO-4 | 938.12 | 38.6 | 899.5 | 38.1 | 900.0 | 0.5 |
| IO-5 | 934.82 | 33.4 | 901.4 | 32.5 | 902.3 | 0.9 |
| IO-6 | 940.59 | 43.2 | 897.4 | 42.6 | 898.0 | 0.6 |
| IO-7 | 936.45 | 38.4 | 898.1 | 37.9 | 898.6 | 0.5 |
| IO-8 | 943.88 | 45.4 | 898.5 | 45.7 | 898.2 | -0.3 |
| IO-9 | 940.94 | 39.3 | 901.6 | 38.8 | 902.1 | 0.5 |
| IO-10 | 940.96 | 39.4 | 901.6 | 39.6 | 901.4 | -0.2 |
| IO-12 | 939.75 | 35.5 | 904.3 | 35.5 | 904.3 | 0.0 |
| IO-13 | 948.93 | 44.9 | 904.0 | 45.0 | 903.9 | -0.1 |
| IO-14 | 932.12 | 29.2 | 902.9 | 28.3 | 903.8 | 0.9 |
| IO-16 | 932.97 | 30.3 | 902.7 | 29.2 | 903.8 | 1.1 |
| IO-17 | 943.79 | 41.3 | 902.5 | 40.9 | 902.9 | 0.4 |
| IO-18 | 954.54 | 50.8 | 903.7 | 50.9 | 903.6 | -0.1 |
| NEW-1 | 937.81 | 35.7 | 902.1 | 36.6 | 901.2 | -0.9 |
| NEW-2 | 943.21 | 41.0 | 902.2 | 41.9 | 901.3 | -0.9 |
| NEW-3 | 953.13 | 46.3 | 906.8 | 46.5 | 906.6 | -0.2 |
| NEW-4 | 957.19 | 53.2 | 904.0 | 53.2 | 904.0 | 0.0 |
| NEW-8 | 950.77 | 49.0 | 901.8 | 48.3 | 902.5 | 0.7 |
| NEW-9 | 955.97 | 47.6 | 908.4 | 49.7 | 906.3 | -2.1 |